Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

SECTION 1. IDENTIFICATION

Product name : Keltan ® 5469C

Product code : 57502764

Manufacturer or supplier's details

Company name of supplier : ARLANXEO Netherlands B.V.

Global Regulatory Affairs and Product

Safety

Address : Urmonderbaan 24

RD Geleen 6167 Netherlands

Recommended use of the chemical and restrictions on use

Recommended use : crude product for the production of technical rubber articles

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS).

GHS label elements

Not a dangerous substance or mixture according to the Globally Harmonized System (GHS).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture :

Mixture

Chemical nature : Ethylene-propylene-diene-rubber (EPDM)

oil extended

Polymer

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (petroleum), hydrotreated	64742-54-7	>= 50 - < 70
heavy paraffinic		

SECTION 4. FIRST AID MEASURES

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash off with soap and water.

Get medical attention if symptoms occur.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if symptoms appear.

If swallowed : Get medical attention if symptoms appear.

Most important symptoms and effects, both acute and

delayed

Skin: Reddening, burning, and possible permanent damage.

Contact with hot material causes thermal skin burns.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam

Dry chemical

Carbon dioxide (CO2)

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Unsuitable extinguishing

media

None known.

Specific hazards during fire

fighting

Toxic and irritating gases/fumes may be given off during burn-

ing or thermal decomposition.

Hazardous combustion prod-

ucts

Carbon dioxide (CO2)
Carbon monoxide

Further information : Promptly isolate the scene by removing all persons from the

vicinity of the incident if there is a fire.

No action shall be taken involving any personal risk or without

suitable training.

Special protective equipment:

for fire-fighters

Fire-fighters should wear appropriate protective equipment

and self-contained breathing apparatus (SCBA) with a full

face-piece operated in positive pressure mode.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

No action shall be taken involving any personal risk or without

suitable training.

Put on appropriate personal protection equipment. Do not touch or walk through spilled material.

Evacuate personnel to safe areas.

Keep unnecessary and unprotected personnel from entering.

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

Methods and materials for containment and cleaning up

Move containers from spill area.

nd cleaning up Vacuum or sweep up material and place in a designated, la-

beled waste container.

Dispose of wastes in an approved waste disposal facility. Do not allow spilled material or wash water to enter sewers,

surface waters, or groundwater systems.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Remove contaminated clothing and protective equipment be-

fore entering eating areas.

Workers should wash hands and face before eating, drinking

and smoking.

Put on appropriate personal protection equipment.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.

Conditions for safe storage : Protect from moisture.

Store in accordance with local regulations.

Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible

materials (see Section 10) and food and drink.

Keep container closed when not in use.

Containers that have been opened must be carefully resealed

and kept upright to prevent leakage. Do not store in unlabeled containers.

Use appropriate container to avoid environmental contamina-

tion.

Recommended storage tem: :

< 86 °F / < 30 °C

perature

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hy- drotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m³	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m³	ACGIH

Engineering measures : Good general ventilation should be sufficient to control work-

er exposure to airborne contaminants.

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

Personal protective equipment

Respiratory protection : Respirator selection must be based on known or anticipated

exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Hand protection

Remarks : Wear suitable gloves.

Eye protection : Safety glasses with side-shields

Skin and body protection : Wear suitable protective clothing.

Hygiene measures : Wash hands, forearms and face thoroughly after handling

chemical products, before eating, smoking and using the

lavatory and at the end of the working period.

Ensure that eyewash stations and safety showers are close

to the workstation location.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : granular

Color : white

Odor : rubber

Burning number : $1 (68 \degree F / 20 \degree C)$

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No specific test data related to reactivity available for this

product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reac-

tions

None known.

Conditions to avoid : Extremes of temperature and direct sunlight.

Incompatible materials : No specific data.

Hazardous decomposition products

Thermal decomposition : Caused by smouldering and incomplete combustion toxic

fumes mainly consisting of CO and CO2 may be developed. Degradation products of the polymers and their additives may

also be formed.

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact

Acute toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : > 5000 ml/kg bw

Method: OECD Test Guideline 402

GLP: yes

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Routes of exposure : Skin contact Species : Guinea pig

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

Result : Did not cause sensitization on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Carcinogenicity - Assess- : Classified based on DMSO extract content < 3% (Regulation

ment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Effects on fertility : Test Type: Fertility

Species: Rat

Application Route: Oral

Frequency of Treatment: 28 daily

Fertility: NOAEL: 1.000 mg/kg body weight

Symptoms: No effects on fertility.

Test Type: Fertility

Application Route: Inhalation Remarks: No data available

Test Type: Fertility Species: Rat

Application Route: Skin contact Frequency of Treatment: 28 daily

Fertility: NOAEL: 1.000 mg/kg body weight

Symptoms: No effects on fertility.

STOT-single exposure

Not classified based on available information.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Assessment : May cause respiratory irritation.

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit
NOAEL : 200 mg/kg
Application Route : Skin contact
Exposure time : 28 d

Exposure time : 28 d

Dose : 200 mg/kg

Remarks : Chronic toxicity

Species : Rat
NOAEL : 0,21 mg/l
Application Route : Inhalation
Exposure time : 28 d
Dose : 0,21 mg/l
Remarks : Chronic toxicity

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Under the recommended processing conditions small

amounts of emitted substance (e.g. residual monomers, residual solvents, decomposition products) may be discharged. According to our experience and information the product has

no harmful effects on health if properly handled.

The substance(s) listed in Chapter 3 is/are encapsulated in this preparation in a polymer and is/are therefore not bioavail-

able.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic tox-

icity)

Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other : Remarks: No toxicity at the limit of solubility.

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

aquatic invertebrates (Chronic toxicity)

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 5.000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 1.000

mg/

Exposure time: 96 h

Persistence and degradability

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : Result: Inherently biodegradable.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

The product is practically insoluble in water. In view of its consistency and insolubility in water, no ecological problems are to be expected if the product is properly handled. This product

is not readily biodegradable.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

RCRA - Resource Conservation and Recovery Authoriza-

tion Act

: If discarded in its purchased form, this product would not be a hazardous waste either by listing or by characteristic. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classification.

fied as a hazardous waste. (40 CFR 261.20-24)

Waste from residues : The generation of waste should be avoided or minimized

wherever possible.

Waste disposal should be in accordance with existing federal,

state, provincial and/or local environmental controls.

This material and its container must be disposed of in a safe

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

way.

Empty containers retain product residue; observe all precau-

tions for product.

Avoid dispersal of spilled material and runoff and contact with

soil, waterways, drains and sewers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)
Hexane	110-54-3	5000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Massachusetts Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7 Ethylene Propylene Diene Rubber 25038-36-2

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including Hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Any chemical(s) listed above which do not appear elsewhere on this SDS are contained in this product at concentrations below 0.1%.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : On TSCA Inventory

TSCA list


No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard.

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

OSHA Z-1 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC -No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Preven-

Keltan ® 5469C



Version Revision Date: SDS Number: Date of last issue: -

1.1 06.02.2020 103000007447 Date of first issue: 26.03.2019

tion; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 06.02.2020

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN